

COMMODITY SPECIFICATION:

QATAR SPECIFICATION

| Component / Substance | Permissible limits |
|------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| Gross Heating Value (GCV) range | 9,340 – 10,420 Kcal/SCM (1,050 – 1,170 BTU/SCF) |
| Methane | not less than 85.0 Mol % |
| Ethane | not more than 9.2 Mol % |
| Propane | not more than 3.00 Mol % |
| Butanes and heavier | not more than 2.00 Mol % |
| Pentanes and heavier | not more than 0.25 Mol % |
| Nitrogen | 1.0 molecular % |
| Total Sulphur | 10.0 ppm (w) |
| Sulphur in form of Hydrogen Sulphide | 10.0 ppm (w) |
| Maximum variation in Wobbe Index (WI) [WI = LHV (Volumetric Basis / (Specific Gravity w.r.t. Air)0.5] | +/- 5.0 % |
| Contaminants | |
| (a) Trace Metals | |
| i. Pb + Zn | 0.50 ppm (w) |
| ii. Na + K | 0.30 ppm (w) |
| iii. Vanadium | 0.50 ppm (w) |
| iv. Calcium | 2.0 ppm (w) |
| v. Magnesium | 2.0 ppm (w) |
| vi. Sum of heavy metals (Hg+V+Pb+Zn+Ni+Others) | 1.0 ppm (w) |
| (b) Solids / Particulates | |
| i. Total for particle size up to 10 micron | |
| ii. For 2 micron < d < 10 micron | 20.0 ppm (w) |
| iii. For particle size greater than 10 micron | 1.50 ppm (w) |
| | 0.30 ppm (w) |
| (c) Liquid contents | Nil |
| (d) Moisture | 112 kg/million SCM |
| Hydrogen content | 1.00 % (by volume) |
| Acetylene (C2H2) | 0.10 % (by volume) |
| Higher Hydrocarbons for | 10.0 % (by volume) |

RUSSIA SPECIFICATION

| LNG SPECIFICATIONS | | |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|---------------------|
| RUSSIAN ORIGIN LIQUEFIED NATURAL GAS | | |
| A. GROSS HEATING VALUE (VOLUME BASED) | Minimum | 1050 Btu/SCF |
| | Maximum | 1170 Btu/SCF |
| B. HYDROCARBON COMPOSITION AND NITROGEN CONTENT WITHIN THE FOLLOWING RANGE | Methane | 85.00 MOL% Minimum |
| | Butanes and Heavier | 2.0 MOL% Maximum |
| | Pentanes and Heavier | 0.10 Mol% Maximum |
| | Nitrogen | 1.00 MOL% Maximum |
| C. IMPURITIES WITH THE FOLLOWING RANGE | Hydrogen Sulphide | 4.8 MG/Nm3 Maximum |
| | Total Sulphur | 28.0 MG/Nm3 Maximum |
| SOLIDS AND OTHER IMPURITIES | None as such quantities as shall interfere with receipt and transportation of LNG, or the use of LNG as natural Gas. | |

PROPOSED QUANTITY DISTRIBUTION AND SHIPMENT:

1st 2nd 3rd 4th SHIPMENTS AT 500,000 MT PER MONTH

5th 6th SHIPMENTS AT 1,000,000 MT PER MONTH

7th 8th SHIPMENTS AT 2,500,000 MT PER MONTH

9th SHIPMENT AT 3,500,000 MT PER MONTH

10th SHIPMENT AT 4,500,000 MT PER MONTH

11TH & 12TH to 60TH SHIPMENTS AT 5,000,000 MT PER MONTH

CONTRACT PAYMENT TERM: Buyer will issue 100% AT SIGHT STANDBY LETTER OF CREDIT {SBL} which should be irrevocable, divisible, confirmed, non-transferable, unconditional and unrestricted for **12+1 consecutive months** to sellers' Bank Issued by one of the TOP 25 First World Banks, with a guarantee of TOTAL FUNDS. This guarantee should be issued by the bank of the Buyer and sent directly to the bank of the Sellers.

Payment is made via SWIFT MT 103 AGAINST all shipping documents including SGS certificate for quality and quantity.